



Maximizing Accuracy and Productivity with Trimble GPS

Presented by

Del Stewart

CompassTools, Inc.

Del Stewart
Regional Sales Manager
Office 303 627-1810
Mobile 507 993-1668

dstewart@compasstoolsinc.com

www.CompassToolsinc.com

Materials – Electronic Format

http://www.compasstoolsinc.com/events/ND_GIS_Users.htm

Agenda

- Increase GPS Accuracy for existing equipment
 - Garmin, GeoXT, GeoXH
 - H-Star Technology
 - Hardware, Infrastructure advances to increase Accuracy
- Increase Productivity
 - Training
 - Hardware
 - Software
 - Peripherals
 - Workflow

■ Garmin

- Download and use Trimble Mission Planning
 Software
 - » http://www.trimble.com/planningsoftware_ts.asp
- Recognize Limitations of Configuration
 Settings
- Avoid High-Multipath Environments

GeoXT

- Hurricane Antenna, Pole, Bipod Legs
- Configuration Settings
- Mission Planning Optimum satellite availability and configuration
- Avoid high-multipath environments whenever possible
- Use Offsets instead of going under canopy or up tight to building

GeoXT


- ArcPad real-time source other than WAAS, or post process
- Baseline length search out closer base station providers
- Understand WGS84/NAD 83 shift for PP, verify base provider ref coord
- Use additional receiver as temporary base station
- Carrier processing/Longer occupation times


- GeoXT suggestions
 - Recognize common sources of error
 - Occupy known control points to verify accuracy
 - Use Survey receivers w/GeoXT running
 TerraSync for cm GIS data collection

■ Monitor sun spot activity:


http://solarscience.msfc.nasa.gov/SunspotC

ycle.shtml





- GeoXH
 - H-StarTechnology



■ GeoXH

- Extra data (L2) collected to measure rather than model Ionospheric conditions
- Sub-foot, 20cm 30cm
- Short occupation times, 2-10 min carrier lock
- Estimated Post Processed Precisions on screen

■ GeoXH

- Single Base Provider up to 60km
- Allows longer baselines (up to 300km) using multiple Base Station Providers
- Even distribution of base providers
- Ensure that base stations have same datum for reference coordinate*
- Accuracy summary report after PP

*webinar coming in November on this topic

GeoXH suggestions

- Use Zephyr Antenna, Pole, BiPod Legs
- Occupy known control points
- Export metadata to back up accuracy and provide QC

- Training
- Managers' Training
- Specialized workshops
- Webinars: How to Crop & Install Mr Sid background files to TerraSync, 10/17/07
- Use resources available
 - Trimble website
 - Trimble Dealers
 - Other users

- Equipment:
- Ensure Trimble hardware has latest firmware
- □ Find proper hardware configuration –
 ProXT/ PF XB with laptop, tablet, mobile,
 PDA or Geo/Juno for application
- Select hardware that best supports software
- Leverage WM5/6 OS

■ Software:

- Use software that best fits workflow
 - » ArcPad, TerraSync, CartoPac, SoloField, other??
- Ensure that your Trimble software has all the latest updates (Call your dealer, or look on Trimble site)
- Import shapefile to automate creation of data dictionary
- Plan and Streamline flow of DD

■ Software

- Take existing shapefile data into field to verify information or reduce data entry or to verify location
- Use navigation function
- Use map display and background imagery to verify accuracy and completeness of data before returning to office

- Software Tips Data Collection
 - Nest features within lines
 - Use Repeat Function to reduce data entry



Peripherals:

- Use laser to reduce walking
- Use camera to gather data faster, tracklog and software, audio notes for attributes
- Integrate images whichever way works best for workflow
 - » Push to GPS
 - » Merge GPS and images back in the office
 - » Record audio notes to streamline field data capture

- Processing
 - Batch Processor
 - Batch Processor
 - Batch Processor

Questions...??

Any Other Questions...??